



Supplied by: Langendorf Supply Company Inc.



www.langendorfsupply.com






2" Standoff Collars with Damper

Sheet Metal Connectors' standoff collars are fabricated from galvanized steel. These collars have a crimp and stop bead on one end. The volume damper is made out of 20 ga. galvanized steel with stiffening beads and a continuous 3/8" aluminum square shaft for strength and rigidity. Nylon end bearings are added to each end to reduce air leakage. All standoff collars have a 3/8" dial regulator eleveated 2" for insulation.

Sleeve with 2" Standoff

Order as follows: A = Diameter






A	Length
6"	6 3/16"
7"	6 3/16"
8"	6 3/16"
9"	6 3/16"
10"	6 3/16"
12"	8"
14"	12"
16"	12"
18"	13"
20"	15"

E-Z Tap Collars with 2" Standoff

Order as follows: A = Diameter All Fittings are 1.75" from Bead to End of Fitting.






	Overall
A	Length
5"	5"
6"	5"
7"	5"
8"	5"
9"	5"
10"	5"
12"	7"
14"	7"
16"	7"
18"	10"
20"	10"
22"	10"
24"	10"

Conical E-Z Tap with 2" Standoff

Order as follows: A = Diameter *Complete Seal Standard






	Overall
Α	Length
6"	9 1/4"
8"	9 1/4"
10"	9 1/4"
12"	9 1/4"

Super Heto with 2" Standoff

Order as follows: A = Diameter





	Overall
Α	Length
6"	8"
8"	9"
10"	9"
12"	9"
14"	9"

All Fittings are 1.75" from Bead to End of Fitting.



